Results from a subkeV energy threshold spherical gazeous detector for light Dark Matter identification


G Gerbier IRFU Saclay

+ I Giomataris, J Derre, P Magnier, A Dastgheibi, D. Jourde, M Gros, E Bougamont, XF Navick, T Papaevangelou, J Galan, G Tsiledakis IRFU P Loaiza, T Zampieri LSM

Principles of detector
Results of calibrations at low energy
Preliminary results in low RA environment
Prospects: physics / development

September 9th 2013 Monterey, TAUP2013


Spherical Proportional Counters



- Sphere cavity + spherical sensor + HT
- => Low threshold (low C), does not depend on size
- Fiducial volume selection by pulse risetime
- Flexible (P, gaz)
- Works in sealed mode
- Large volume => 10's kg possible
- 2 LEP cavity 130 cm Ø tested
- Digitisation at 2 MHz + soft trigger



Spherical Proportional Counters



Sphere cavity + spherical sensor + HT

=> Low threshold (low C), does not depend on size

Fiducial volume selection by pulse risetime

Flexible (P, gaz)

Works in sealed mode

Large volume => 10's kg possible

2 LEP cavity 130 cm Ø tested

Digitisation at 2 MHz + soft trigger

1 low activity 60 cm Ø in operation @ LSM




Run with Ar/CH₄ + 3g 3 He @ 200 mb SPC 130cm Ø @ LSM


NB: no start => risetime records place and/ or history of energy deposition

If **point like** energy deposition, rise time depends only on radius of interaction (diffusion)

If **track**, rise time depends on orientation of track, ie on difference of drift times




Run with Ar/CH₄ + 3g 3 He @ 200 mb SPC 130cm Ø @ LSM




Going to low energy: calibration with ³⁷Ar source for volume response (SPC 130cm Ø @ Saclay)

- ³⁷Ar, EC, 35 days lifetime, Kα 2.6 keV and Lβ 260 ev
- Source made by n,α from Calcium salt powder irradiated with fast neutrons
- => Calibration show homogenous volume response







Calibration with UV flash pulsed lamp for single electron response




250 mb, Ar+2%CH4 HV = 3100 V14 mm sensor



Pulse shape



Trigger @ 10 ADU




Delta time (UV-sphere pulse) Look for pulse in 200-260 µs window About 1 in 10 => single electron response


> **Trigger efficiency for** single electron = 54 % NB: single electron in Ar gaz w ≈ 30 eV => Threshold = 20 eV


Light dark matter search : low activity 60 cm Ø

prototype @ LSM in Pb/PE shield

- In test since september 2012
- Test of sensors from 14 mm to 6 mm
- Reduction of RA contaminants
- Commissionning runs
 - Argon (but ³⁹Ar intrinsic radioactivityy)
 - Neon @ 2-4 bars
 - Neon/He 50/50 @ 2 bars









Light dark matter search : low activity 60 cm Ø


prototype @ LSM in Pb/PE shield

- In test since september 2012
- Test of sensors from 14 mm to 6 mm
- Reduction of RA contaminants
- Commissionning runs
 - Argon (but ³⁹Ar intrinsic radioactivityy)
 - Neon @ 2-4 bars
 - Neon/He 50/50 @ 2 bars











Light dark matter search : low activity 60 cm Ø


prototype @ LSM in Pb/PE shield

- In test since september 2012
- Test of sensors from 14 mm to 6 mm
- Reduction of RA contaminants
- Commissionning runs
 - Argon (but ³⁹Ar intrinsic radioactivityy)
 - Neon @ 2-4 bars
 - Neon/He 50/50 @ 2 bars












Additional discrimination through single/multiple energy deposition



Test run with Ne (2bars)+He (2bars) 8h

He gives longer drift times => better identification of multiples






⇒ Studies in progress:

- refined pulse analysis
- calibration with fast neutron
- simulation of pulse shapes of electrons and neutrons
- Reduce RA contamination (alpha from ²¹⁰Po too high by factor 100)

Sensitivity curves for light WIMP's



Other applications

- Axion Like Particle detection: (decays in 2 photons inside sphere volume) motivation: solar corona temperature problem L. Di Lella, K. Zioutas, Astropart. Phys. 19 (2003) 145(J Galan)
- Thermal and fast neutron detection: interest: containment of products of capture eg He3, other gaz studied
- Network of 4m Ø spheres for SuperNovae neutrino detection through coherent scattering (about 10 evts for SN @10 kpc for 10 atm Argon =600 kg)
- Measurement of neutrino coherent scattering at reactor ...


Measuring coherent neutrino scattering at nuclear

reactor within reach

 Simulation of expected spectrum from nuclear reactor, on Ar, with quenching factor and instrumental response to single electron

Sphere of 2 m diam, 5 bars

| Parameters | | | |
|--------------------|-------|------|----------|
| Power of reactor | | 0,07 | GW |
| Distance to core | | 7 | m |
| Radius of sphere | | 1 | m |
| Pressure | | 5 | atm |
| Gaz | argon | 37,4 | kg |
| Signal nucoh >=2 e | | 198 | evts/day |
| Delta F · 2-6e | | 0.12 | keV |







proto collaboration

New Experiments With Spheres
Neutrino Experiments With Spheres
New Experiments for Wimps with Spheres

CEA-IRFU/Saclay (GG,IG),LSM (F Piquemal), Aristotle University of Tessaloniki (I Savvidis), University of Ioannina (I Vergados), NCSR DemoKritos (G Fanourakis), Hellenic Open University (S Tzamaria)

University of Tsinghua Beijing (C Tao), Shanghai Jiao Tong University (K Ni), IHEP-Beijing (Z Wang, C Yang)

University of Saragoza (I Irastorza), Livermore (JR Armendariz)

Projects under study

- 4 m Ø underwater 2000 m @ Pylos @ few 100s bars for SN
- 2 m Ø underground low activity for DM and ALP search shielded in water tank
- Perform v coherent scaterring expt
- Develop neutron spectrometer
- Develop sensors + scint light detection
- + Great tool for training to particle detection!



Conclusions/outlook

- First studies show that spherical gaz detector :
 - can indeed reach single ionisation electron sensitivity @ P>1 atm
 - has background rejection capabilities and redondancies to identify signal
 - is well adapted for low mass WIMP search 0.1 to 5 GeV
 - has potential for neutrino coherent scattering detection & other LE rare processes
- Developments to improve performances of current prototype
 - Decrease high radioactive contamination : surface Rn descendants
 - Improve pulse shape analysis : calibration, templates...
 - Perform calibration with neutron/Ar37
 - Perform quenching factor measurements in <keV region (D Santos installation at Grenoble)
- Going to larger volume/pressure :
 - NB : 4 m diameter sphere can hold 600 kg of Ar @ 10 bars
 - Decoupling of amplification from drift: new ideas about sensors currently tested
 - ... lot to develop and discover